K 103 TECH

www.kraiburg-austria.com

09/2025

BESCHREIBUNG

» Blockprofil mit geschlossenen Schultern und wings
» Hohe Stabilität gegen seitliche Scherkräfte durch wings
» Bereifung für Auflieger und Anhänger
» Einsatz im Nah- und Baustellenverkehr
» Wings beugen Ablösungen zwischen Lauffläche und Karkasse vor
» Richtungsstabil durch geschlossene Schultern
» Sehr gute Selbstreinigung
» Gute Übertragung von Traktionskräften durch massive Profilblöcke in der Laufflächenmitte

BESONDERHEITEN

Profiltiefe 18mm

FEATURES

» Block-type tread with closed shoulders and wing edges
» Good stability against lateral shearing force due to closed shoulders and wing edges
» Tires for semi-trailer and trailer
» For use on short traffic and off road
» Wing edges help prevent tread separating from the casing
» Straight-running stability due to closed shoulders
» Very good self-cleaning
» Good transfer of traction forces due to solid tread blocks in the center of pattern

NOTES

Skid depth 18mm

Die Metergewichte und Profiltiefen können produktionsbedingt um +/- 2 % variieren.
* Zum Microprofilieren geeignet

Weight per meter and profile depth may vary by +/- 2 % according to production batch.
* Also available as micro siped

mm	mm	mm	kg/m	m
295	325	18,0	6,19	3,29/A

TECHNISCHE DATEN
Technical details

KRAIBURG

WWW.KRAIBURG-AUSTRIA.COM