



THE ECOLOGICAL SOLUTION FOR RETREADING

PRODUCT INFORMATION

PERIVALLON

- ➔ Water-based solution - manages completely without solvents
- ➔ Very low application quantity - reduced storage space
- ➔ No danger of explosion - no hazardous goods store required
- ➔ Little cleaning effort - very low cleaning costs for the spray booth, spray gun and extraction system filters
- ➔ Considerably less stress for employees and the environment
- ➔ Disposal of empty containers - no special waste


With the continuously increasing legal demands on environmental protection, operational reliability and employee protection, retread companies are increasingly facing great challenges these days. KRAIBURG has the perfect solution here.

Basis

Application quantity cold:
Application quantity hot:
Drying time:
Room temperature:
Appearance:
Shelf life:
Release:

Water-latex solution

approx. 20 g/tyre
approx. 35 g/tyre
5 to 8 minutes depending on the room temperature
at least 15 °C
white on application, transparent after drying
9 months
Only with the use of KRAIBURG retread materials



Recommended spraying device: PERIVALLON spray system 10 I

Note: Observe the exact application quantity. A higher application quantity will lead to poorer adhesion. Please arrange a training appointment for your production staff with your responsible KRAIBURG TSC technician before using PERIVALLON for the first time.

